

Digital room corrector

- Wire version (2 wires, connection to CM2K module)
- Wireless version (connection on WiFi-box connected to the boiler)
- Changing set room temperature
- Basic control of the boiler
- Set of timers
- Weather forecast...



CSK (analog room corrector)

- Possibility of set room temperature correction (according room temperature set on boiler regulation)
- Possibility to turn off heating circuit where room corrector is installed
- It can be connected only to the CM2K module and BioTec-L boiler.



CSK

CM2K (additional heating circuits control)

- Possibility to control up to 2 heating circuits according to outside temperature and heating circuit curve (controlling up to 2 mixing valves with motor actuators and up to 2 heating circuit pumps or up to 2 DHW circuits or up to 2 recirculation circuits or up to 2 DHW circuits+recirculation).
- Possibility to connect up to 2 room correctors (additional equipment)
- Possibility to connect up to 4 CM2K modules (8 heating circuits)
- Possibility of connection to the PelTec, BioTec-L, BioTec Plus, Cm Pelet-set Touch, EKO-CSK P UNIT, EKO-CSK Multi Plus



CM2K

CM WiFi-box (boiler monitoring and controlling through internet)

- Possibility of boiler monitoring with the PC, mobile phone, laptop, etc.
- Possibility to turn on / turn off boiler, temperatures adjustment, warning and error alarms by the PC, mobile phone, laptop, etc.
- Possibility of connection to the PelTec, Cm Pelet-set Touch, EKO-CSK P Unit, EKO-CSK Multi Plus boilers.



CM Wifi-box

CM-GSM (boiler status information through SMS messages)

- Request for the boiler status phase of work, boiler temperature, through an SMS message in the selected language
- Notification of the boiler status through the mobile network text message or call (errors, warning..)
- Boiler start/stop by SMS
- Possibility of internet connection through mobile data connection (GPRS, SIM card with enabled call and mobile data connection is necessary).
- Possibility of connection to the PelTec, BioTec-L, BioTec Plus, Cm Pelet-set Touch, EKO-CSK P UNIT, EKO-CSK Multi Plus



CM-GSM

CAL (error and warning sound and light information)

- Module for sound or light information about boiler error and warning
- Possibility of connection to the PelTec, BioTec-L, BioTec Plus, Cm Pelet-set Touch, EKO-CSK P UNIT, EKO-CSK Multi Plus boilers



CAL

CMNET (boiler cascade connection)

- Possibility to cascade control 2 to 8 boilers
- For cascade of 2 boilers = 1x CMNET, for cascade 3 to 8 boilers = every boiler one CMNET
- Connection to the boilers by UTP cables
- Possibility of connection to the PelTec, BioTec-L, BioTec Plus, Cm Pelet-set Touch, EKO-CSK P UNIT, EKO-CSK Multi Plus boilers



CMNET